

THE NEXT GEN ECANTER IS FUSO'S LATEST ELECTRIC TRUCK, WITH A NEW FACE LIFT ON BOTH THE INTERIOR AND EXTERIOR AND A WHOLE RANGE OF OPTIONS THE NEXT GEN IS READY FOR ANYTHING.

GVM BATTERY SIZE POWER/TORQUE

6000кg 83кwh 110кw / 430 Nm

- Zero Exhaust Emissions
- Full Safety Package



ECANTER SPECIFICATIONS

MODEL 4X2 6T MWB CITY FEAVKERDSFAB WHEEL BASE 3400mm **GVM (optional)**


Rear Suspension

Туре

Steering Column

6,000kg

Type Permanent magnet synchronous motor S40 Power 110kW peak / 85kW continuous Torque 430Nm peak / 250Nm continuous Cooling Coolant and water mix



| High Voltage Battery | | |
|----------------------|--|--|
| Туре | LFP lithium iron phosphate | |
| Capacity | 83kWh / 2 battery pack | |
| Cooling | Water & Coolant mix | |
| Charging | CCS2 | |
| AC Charging | up to 22kW (5hrs) | |
| DC Charging | up to 104kW (0.73hrs) | |
| Notes | *Charging times are based on theoretical numbers | |

| Electrical | |
|---|--|
| 12V / 24V with Battery Equalizer | |
| 24V 80Ah + 60Ah with equalizer for Body Builder | |
| LED | |
| LED | |
| LED | |
| | |

| Transmission | |
|--------------|---------------------------------------|
| Version | Single Reduction Gearbox |
| Type/Speeds | 1 speed |
| Features | No Gear Changes In-Dash Gear Lever |
| Ratios | 1:19.528 |

| Type | Coil spring type independent suspension |
|------------|---|
| Capacity * | 2600kg |
| Notes | *See MAX LOADING for vehicle capacity. |

Coil springs with shock absorbers

| Rear Axle | |
|-----------|--|
| Туре | De Dion tube (eAxle) |
| Capacity* | 4500kg |
| Notes | *See MAX LOADING for vehicle capacity. |

| Туре | Laminated leaf springs with shock absorbers |
|-------------|---|
| Max Loading | |
| Front | 2600kg |
| Rear | 4500kg |
| Total | 6000kg |
| | |
| Options | |
| Options | Q02 - ePTO Flange system + Cab back control Q03 - ePTO Pulley system + Cab back control |
| | |
| Steering | |

| Brakes | |
|------------|---|
| Туре | Hydraulic Dual Circuit with Front and Rear Discs |
| Features | ABS plus EBD Electronic Brake Distribution ABA5 Active Brake Assist 5 |
| Park Brake | Electric park brake - disc park brake |
| Auxiliary | 4 Stage regenerative brake |

Rack & Pinion with Integral Power Assistance

Tilt/Telescopic Adjustable with Lock

| Wheels & Tyres | | |
|--------------------|-----------------|--|
| Wheel Type | Steel Disc Rims | |
| Wheel Size | 17.5X5.25-115-8 | |
| Wheel Stud Pattern | 5 Stud | |
| Tyre Size All | 205/75R17.5 | |
| Spare Tyre Carrier | Provided | |
| Spare Tyre | Provided | |

| Chassis | |
|---------|---|
| Туре | Ladder frame, channel section with reinforcement and crossmembers |
| Width | 700mm |
| | |

| Instruments | |
|-------------|--|
| Gauges | New Digital Display Speedometer Braking Mode Battery Percentage Range Temperature |
| | |

| Airbag(s) | Driver's Air Bag |
|-----------------------|--|
| Cab Cooling & Heating | Air Conditioner / Heater / Demister |
| Accessory Power | 12V Accessory Power Outlet / Cigar Lighter |
| Driving | Fuso Multimedia Unit |
| | Keyless Central Locking |
| | Electric Windows |
| | Cup Holders 2 |
| | 3 seats |



Туре

MODEL

Service Intervals

4X2 6T MWB CITY FEAVKERDSFAB

WHEEL BASE 3400mm

GVM (optional) 6,000kg

| Cab Features | |
|-------------------|---|
| Туре | All Steel Forward Control Manual Tilt |
| Cab Structure | ECE-R29 Standard |
| Colour | Natural White |
| Interior | Fully Trimmed |
| Windscreen | Laminated Tinted |
| Windscreen Wipers | 2 Speed + Intermittent Cycle with Integrated Washer Nozzles |
| Seating Capacity | 3 |
| Seat Belts | 2 x 3 point seat belts |
| | 1 x 2 point lap sash |
| Seat (driver) | ISRI seats with arm rest & lumbar support |
| Seats (passenger) | Flat Folding, ISRI 2 Passenger Fixed Seat |

| | · · · · · · · · · · · · · · · · · · · |
|-----------------|--|
| Active Safety | |
| Safety Systems | ABA5 - Active Brake Assist 5 ASGA - Active Sideguard Assist AVAS - Acoustic Vehicle Alerting System HSA - Hill Start Assist LDWS - Lane Departure Warning System ESP - Electronic Stability Program ABS plus EBD - Anti-lock Braking System plus Electronic Brake Distribution LED Head lamps and Tail lamps DRL - Daytime Running Lamps IHC - Intelligent Headlight Control High Voltage Interlock Loop |
| Reverse Warning | Buzzer |
| Notes | Active Safety Systems primary function is to provide driver assistance to increase road safety in events of |

| Passive Safety | |
|--|---|
| Airbags Body Strength | SRS Airbag - Driver ECE-R29 Cab Strength Compliant |
| Emergency Operational Decals | Internal & External |
| Seat Belts - Driver & Driver Assistant | 3 Point ELR Lap Sash |

safe and alert driving.

driver inattentiveness. These systems do not allow for lack of attention whilst driving and should not replace

| Interval* | 30,000km or 12 Months (whichever occurs first) |
|------------------|--|
| Warranty* | |
| Basic/Powertrain | 5 Years / 200,000kms |
| | 8 Years / 200,000kms HV Battery Only |
| Notes | * Please refer to Fuso Owners Warranty Booklet for additional terms and conditions. |


| Performance | |
|--|---|
| Turning Circle (kerb to kerb - metres) | 12.8 |
| Electronically Speed Limited to: | 100km/hr |
| Gradeability at Rated GVM (theoretical)* | 20% |
| Notes | *This is theoretical performance only. Actual performance may vary under different conditions |

| Mass estimated* | |
|-----------------|--|
| Front* | 1655kg |
| Rear* | 1415kg |
| Total* | 3070kg |
| Notes | * Mass est. includes weight of oil, coolant, spare tyre carrier & bracket, spare tyre & disc wheel. Weights provided are subject to 3.5% variation +/- |

| Dimensions mm | |
|---|------|
| WFF (Width Front Fender) (mm) | 1695 |
| WRA (Width Rear Axle) (mm) | 1880 |
| WFT (Width Front Track) (mm) | 1390 |
| WRT (Width Rear Track) (mm) | 1435 |
| Width Frame (mm) | 700 |
| A - Length Overall (mm) | 5785 |
| C - Front Overhang (mm) | 990 |
| D - Wheelbase (mm) | 3400 |
| G - Front Axle to Rear of Cab (mm) | 525 |
| H - Rear of Cab to Rearmost Item Behind Cab (mm) | 94 |
| I - Rearmost Item Behind Cab to Rear Axle (mm) | 2781 |
| J - Frame, Rear Axle to End (mm) | 1395 |
| P - Height Cab to Ground (mm) | 2155 |
| Q - Height Cab to Frame (mm) | 1470 |
| R - Height Rear Frame to Ground (mm) | 750 |









ECANTER SPECIFICATIONS

MODEL 4X2 6T MWB CITY FEAVKERDSFAB WHEEL BASE 3400mm

GVM (optional) 6,000kg



or visit fuso.com.au

Unless specified in writing herein the accessories, applications, bodies or equipment depicted in this are for illustration purposes only and may not be available from Daimler Truck Australia Pacific Pty Ltd. ABN 86 618 413 282 DTAuP. No representation or warranty whatsoever is given in relation to any accessories, applications, bodies or equipment or suitability of same that are shown herein that may be manufactured, supplied or fitted by a party other than DTAuP. DTAuP reserves the right without notice or obligation to discontinue or make changes to the colour, designs, materials and specifications of the products and options referred to herein at any time. For the most current information and in order to ascertain which accessories, applications, bodies and equipment are available from DTAuP please contact your authorised FUSO dealer. Fuso is a registered trademark of Daimler Truck Australia Pacific Pty Ltd. Copyright DTAuP. Reproduction in whole or part prohibited without written approval. Valid from 20-Jun-23.

